

INSIGHTS



Product News | Information | Updates

Key Specifications

-  Maximum lift capacity
3,000 kg (6,614 lb)
-  Maximum lifting height
6.89 m (22 ft 7 in)
-  Maximum capacity at forward reach
1,000 kg (2,205 lb) at
3.99 m (13 ft 1 in)
-  Weight
5,970 kg (13,161 lb)

Introducing the newly redesigned Genie® GTH™-3007 telehandler

Most compact unit in its category provides full-sized performance at right-sized price for high return on invested capital (ROIC)

Providing fleet owners the versatile on-site productivity and cost-efficiency you need at a market-beating price, the new Genie® GTH™-3007 telehandler combines efficient, full-featured capabilities with the most compact dimensions and lightest machine weight in its category. The Genie GTH-3007 compact telehandler will be available in January 2019.

Power matched to your business needs

Boasting a maximum lift capacity of 3,000 kg (6,614 lb), a vertical reach capacity of 2,500 kg (5,511 lb) at a maximum height of 6.89 m (22 ft 7 in), and a horizontal reach capacity of 1,000 kg (2,205 lb) at 3.99 m (13 ft 1 in), this new unit comes with the benefits of a low-emissions 74-hp Deutz Stage IIIB (Tier IV Final) compliant engine to provide operators productive capacity and rapid rental returns on investment.

The Genie GTH-3007 telehandler provides an impressive rental rate for its compact nature, with its less complex machine design improving the overall ROIC for owners, making it perfect for the rental market. This new telehandler also offers owners the peace of mind of a fully compliant and low emissions operation without the need of Diesel Exhaust Fluid (DEF) after treatment.



Call 1800 788 633
www.genielift.com.au



In addition to offering a vertical reach up to the equivalent of three floors, this productive and versatile telehandler is well suited to an extremely wide variety of outdoor lifting, carrying, loading and placement duties

Main Features:

- Optimised transport costs with three units on one standard truck
- Great ground clearance of 45 cm (18 in) and rugged terrainability
- Full-time 4-wheel drive
- Variable speed hydrostatic transmission
- Industry-leading 74-hp Deutz Stage IIIB (Tier IV Final)
- Narrow 2 m (6 ft 6 in) width
- Compact 2.07 m (6 ft 9 in) height
- 2.55 m (8 ft 4 in) inside turning radius
- Standard Dana® axles with dual brakes
- No Diesel exhaust fluid, exhaust filter or regen
- Parts commonality across Genie telehandler line

Applications:

This productive, versatile and hydrostatic telehandler is well suited to an extremely wide variety of outdoor lifting, carrying, loading and placement duties in:

- General construction
- Waste-handling
- Recycling
- Materials-handling
- Demolition

Genie
A TEREX BRAND



Fast and precise load positioning capabilities to pick and carry loads

At home on any jobsite

As the heavier lifting, higher reaching brother of the Genie GTH^T-2506 compact telehandler, at the low weight of 5,970 kg (13,161 lb) the new Genie GTH-3007 telehandler shares the same rugged durability common to all other six models of the Genie GTH telehandler family.

The Genie GTH-3007, equipped with a multi-functional proportional joystick, is the perfect tool for loading and unloading, moving and placing, and jobsite preparation and cleanup. You'll instantly recognise its new contemporary Genie blue styling, which stands out on any jobsite.

This telehandler is one of our compact models and is at home on any jobsite — offering versatility from general residential and commercial construction work to more specialty applications such as masonry projects. Its compact dimensions offer a machine length at front wheels of 4.06 m (13 ft 4 in), a machine width of 2 m (6 ft 6 in) and a machine height of 2.07 m (6 ft 8 in) making the Genie GTH-3007 unit the perfect match for jobs on busy and congested sites in confined or difficult to access spaces. Optimising transport costs, the combination of low weight and short machine length enable three units to be carried on one standard truck.

Built-in value

And, there's no stopping this powerful performer: Full-time 4-wheel drive and 4-wheel steering enable your customers to drive easily on hills and slopes up to 30% gradeability and in rough terrain. Combining the durable 'built-to-last' quality and

serviceability features that Genie products are known for, this telehandler includes a rugged chassis, a two-stage boom with no chains or cables, durable heavy-duty steel fenders and field proven Dana® axles with dual brakes that make the unit easy to steer and manoeuvre around any worksite.

Superior serviceability

Servicing is also notably faster and easier than units with higher horsepower engines which enhances rental availability and boosts profitability. Equipped with a variable speed hydrostat transmission for a smooth and powerful drive, this unit features a side-mounted engine cover with a comfortable opening angle for easy filter replacement, access to engine components and hydraulic test ports located at the front of the chassis. For attachment flexibility, the Genie GTH-3007 telehandler comes with an optional auxiliary hydraulics Quick Attach carriage, a feature that the model shares with the Genie GTH-2506 compact telehandler.



Industry-leading 74 hp engine enhances rental availability and boosts profitability

TAKING YOU **HIGHER**
GENIELIFT.COM.AU | 1800 788 633