

### Specifications

| MODEL  | GR-15          |              | GR-20          |              |
|--|----------------|--------------|----------------|--------------|
| Measurements   | Metric         | US           | Metric         | US           |
| Working height*  | 6.47 m         | 20 ft 8 in   | 8.02 m         | 25 ft 9 in   |
| Platform height  | 4.47 m         | 14 ft 8 in   | 6.02 m         | 19 ft 9 in   |
| <b>A B</b> Platform dimensions (length x width)<br>Standard with extension | 1.40 m x 75 cm | 55 x 29.5 in | 1.40 m x 75 cm | 55 x 29.5 in |
| <b>A</b> Height - stowed   | 1.57 m         | 5 ft 2 in    | 1.98 m         | 6 ft 6 in    |
| <b>A</b> Length - stowed   | 1.35 m         | 4 ft 5 in    | 1.35 m         | 4 ft 5 in    |
| <b>A</b> Width   | 75 cm          | 2 ft 5.5 in  | 80 cm          | 2 ft 7.5 in  |
| <b>A</b> Ground clearance - center   | 6.4 cm         | 2.5 in       | 6.4 cm         | 2.5 in       |

### Productivity

|  |                     |               |                |               |
|--|---------------------|---------------|----------------|---------------|
| Max platform occupancy (indoor/outdoor) <sup>1</sup> | 1/-                 |               |                |               |
| Lift capacity  | 227 kg              | 500 lbs       | 159 kg         | 350 lbs       |
| Drive speed - stowed                                 | 4.0 km/h            | 2.5 mph       | 4.0 km/h       | 2.5 mph       |
| Drive speed - raised                                 | 0.8 km/h            | 0.5 mph       | 0.8 km/h       | 0.5 mph       |
| Gradeability**                                       | 30%                 |               |                |               |
| Turning radius - inside                              | zero                |               |                |               |
| Turning radius - outside                             | 1.32 m              | 4 ft 4 in     | 1.35 m         | 4 ft 5 in     |
| Raise / lower speed                                  | 21 / 19 sec         | 21 / 19 sec   | 24 / 21 sec    | 24 / 21 sec   |
| Controls   | 24V DC proportional |               |                |               |
| Tyres - solid non-marking                            | 25 x 8 x 20 cm      | 10 x 3 x 8 in | 25 x 8 x 20 cm | 10 x 3 x 8 in |

### Power

|                           |                                |         |        |         |
|---------------------------|--------------------------------|---------|--------|---------|
| Power source              | 24V (four 6V 225 Ah batteries) |         |        |         |
| Hydraulic system capacity | 8.33 L                         | 2.2 gal | 8.33 L | 2.2 gal |

### Sound & Vibration Levels




|   |                       |                         |                       |                         |
|---|-----------------------|-------------------------|-----------------------|-------------------------|
| Sound pressure level (ground workstation)   | <70 dBA               |                         |                       |                         |
| Sound pressure level (platform workstation) | <70 dBA               |                         |                       |                         |
| Vibration                                   | <2.5 m/s <sup>2</sup> | <98.4 in/s <sup>2</sup> | <2.5 m/s <sup>2</sup> | <98.4 in/s <sup>2</sup> |

### Weight\*\*\*

|  |         |           |          |           |
|--|---------|-----------|----------|-----------|
|  | 1026 kg | 2,261 lbs | 1,148 kg | 2,529 lbs |
|--|---------|-----------|----------|-----------|

### Standards Compliance

ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10



<sup>1</sup> Indoor use only.  
<sup>\*</sup> The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.  
<sup>\*\*</sup> Gradeability applies to driving on slopes. See operator's manual for details regarding slope rating.  
<sup>\*\*\*</sup> Weight will vary depending on options and/or country standards.

### Features

#### Standard Features

##### Measurements

###### GR-15

- 6.47 m (20 ft 8 in) working height
- 4.47 m (14 ft 8 in) platform height
- Up to 227 kg (500 lbs) lift capacity

###### GR-20

- 8.02 m (25 ft 9 in) working height
- 6.02 m (19 ft 9 in) platform height
- Up to 159 kg (350 lbs) lift capacity

##### Productivity

- Smart Link™ control system (joystick, proportional lift & 2 selectable proportional drive speeds, user-friendly diagnostics)
- Auxiliary platform lowering
- Low 39 cm (15.5 in) platform entry height
- Work station tray (GR-15 only)
- Patented rigid mast system
- Compact base 75 cm x 1.35 m (29.5 x 53 in) (GR-15 only)
- Ground clearance 6.4 cm (2.5 inches) (stowed)
- Battery charge indicator
- On-board diagnostic system
- Descent and tilt alarm
- Zero inside turning radius
- Dual wheel brakes
- Hydraulic brake release
- Pothole protection
- Hinged rear ABS covers for easy access to all major electrical and hydraulic components
- Tie down attachment points
- Overhead crane attachment point
- Large forklift pockets access
- Certified load sensor
- Dual flashing beacons
- Motion alarm
- Automotive-style horn
- Drive cutout while charging

#### Standard Features

##### Platform

- 1.40 m x 75 cm (55 x 29.5 in) platform with 51 cm (20 in) extension and sliding midrail

##### Power

- 24V (four 6V 225 Ah batteries) with automatic 25 amp battery charger

##### Tyres

- Non-marking solid

#### Options & Accessories

##### Productivity Options

- 240 V power to platform
- Biodegradable hydraulic oil

##### Power Options

- AGM maintenance-free batteries



### Genie – Toll free number 1800 788 633

#### Brisbane

HEAD OFFICE

33 Kimberley Street  
Darra QLD 4076

#### Sydney

74 Glendenning Road  
Glendenning NSW 2761

#### Melbourne

374 Hammond Road  
Dandenong VIC 3175

#### Adelaide

16-18 Nixon Road  
Wingfield SA 5013

#### Perth

126 Sheffield Road  
Welshpool WA 6106

#### Darwin

33 McCourt Road  
Yarrowonga NT 0830

#### Genie USA

18340 NE 76th Street  
P.O. Box 97030  
Redmond, Washington  
98073-9730

#### Distributed By:

Effective Date: July, 2015. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2015 Terex Corporation.