



# TRAILER-MOUNTED Z<sup>™</sup>-BOOMS

## **CUSTOMERS FIRST. ALWAYS.**

### **PARTNERING FOR SUCCESS**

Our dedication to lifting you higher extends well beyond the physical reach of our products. We thrive on building satisfying customer relationships founded on the idea of partnership. Because you, our customer, are at the centre of everything we do.

Since 1966, we've been developing products to solve your worksite challenges – and that process never ends. Our team of product managers and engineers uses your input to design new products, featuring the latest technology to meet your changing needs. Then we manufacture those products to stringent standards that help increase quality, lower costs and give you exceptional value for years to come.

### **PROVIDING SUPERIOR VALUE**

Our commitment doesn't end with the sale. Our dedicated service teams are available to provide support when you need it most. Our extensive parts network ships most parts within 24 hours, too. Simply put, we're always working to help maximise your "up time" so you can be more successful.

Genie is driven by one goal: doing the right thing, at the right time for our customers. That's not just what we do; it's who we are. So tell us what you need. We're listening.



**Genie**<sup>®</sup>  
A TEREX BRAND

### **SETTING THE STANDARD**

Genie manufactures some of the most advanced, highest-valued lift equipment in the industry. Genie distinctive blue lifts set the standard for performance and durability – not to mention support from people who understand your business.



## EXTEND YOUR **PRODUCTIVITY**

Genie® trailer-mounted Z™-booms feature an outstanding operating envelope, making them your best value to reach jobs high and low. Both the Genie® TZ™-34/20 and the TZ™-50 feature the exclusive Genie® Automatic Leveling System™ for self-leveling on any terrain, resulting in a faster setup that gets the job started – and finished – quicker. With easy-to-tow mobility and simple pictograph controls, it's no wonder that Genie® trailer-mounted Z™-booms take productivity to new heights.

**Versatile Genie® trailer-mounted Z™-booms offer an outstanding operating envelope with working heights of 12.36 to over 17 m (40 to over 55 ft) and superior outreach of 5.59 to over 8.8 m (18 ft 4 in to over 29 ft).**

# REACH UP, REACH OUT

The Genie® TZ™-34/20 has an outstanding working envelope and intuitive controls that allow operators to efficiently reach where they need to be. With a working height of up to 12.36 m (40 ft), an outreach of 5.59 m (18 ft 4 in) and 4.90 m (16 ft 1 in) of “up and over” capability, the TZ™-34/20 provides excellent versatility for a variety of jobs.

## EASY-TO-USE CONTROLS

Both ground and platform controls feature an easy-to-use pictograph system making it quick and easy to get right to work.



## EASY TRANSPORT AND SETUP

The TZ™-34/20 is easily towed behind a ute or 4WD. Hydraulic outriggers with automatic self-leveling allow machine setup in as little as 40 seconds, so you spend less time setting up and more time working.



**Though rugged and heavy-duty, the TZ™-34/20 is lightweight enough to use on lawns, slate or gymnasium floors. Simply put, it meets the challenges of just about any working environment.**



## DESIGNED FOR SERVICEABILITY

Easy setup and operation aren't the only efficient benefits of the TZ™-34/20. The machine is built to make service simple, including easy access to batteries. Simply release the clamp and remove the cover.

## BUILT TO WORK

Durability is built in. The rigid chassis has a heavy-duty base and robust outriggers, making it the best solution for large and small contractors, maintenance crews, painting contractors and rental yards.



# INDUSTRY-LEADING WORKING RANGE

For the ultimate in reach and range, you can't beat the Genie® TZ™-50. With a working height of 17.09 m (55 ft 6 in), 8.89 m (29 ft 2 in) of outreach and 6.71 m (22 ft) of “up and over” clearance, the numbers speak volumes about the versatility of the TZ™-50. The fact that it's a favorite with contractors and rental yards says even more.



## COMPACT NARROW VERSATILITY

The TZ™-50 offers outstanding “up, out and over” capabilities in a compact, lightweight package that is easy to manoeuvre in congested work areas. An assortment of options and accessories means you can customise the versatile TZ™-50 to meet your exact needs.



**The TZ™-50 provides exceptional value in high reach lift equipment.**



## MOBILITY

The TZ™-50 goes where you need it with easy towing behind a ute or 4WD – and heavy-duty jockey wheels for precise positioning during setup. The optional Drive and Set™ feature allows you to drive the TZ™-50 to where you need to work.




## SIMPLE LEVELING AND CONTROLS

Genie's patent-pending Automatic Leveling System™ allows the operator to hydraulically deploy the outriggers and level the machine to 10° in all directions. Plus, easy-to-use pictographs on both ground and platform controls offer simple, intuitive operation.



## DESIGNED FOR SERVICEABILITY

From transport and setup to operation and service, the TZ™-50 keeps it simple, including easy access to batteries. Simply release the clamp and remove the cover.



## FLEXIBLE WORKING RANGE

Along with the primary jib boom, the articulating jib boom provides an additional 1.25 m (4 ft 1 in) of horizontal reach and 135° of working range to position the platform above or below horizontal.

# OPTIONS AND ACCESSORIES

TZ™-34/20    TZ™-50

PLATFORM OPTIONS		
PLATFORM ROTATION	O	S
POWER OPTIONS		
DC	S	S
HYBRID HONDA CHARGING SYSTEM	-	S
DRIVE OPTIONS		
DRIVE AND SET OPTION	-	O
COUPLER OPTIONS		
5.08 CM (2 IN) BALL COUPLER	S	S
ACCESSORIES		
TOOL TRAY	S	S
FLUORESCENT TUBE CADDY	O	O
BATTERY CHARGE INDICATOR (BCI)	O	O
OPERATIONAL WARNING LIGHT PACKAGE (FLASHING BEACONS)	S	S
NON-MARKING OUTRIGGER FOOTPADS	S	S
SPARE TYRE	S	S
WHEEL CHOCKS	O	O
HORN	S	S
LADDER/STEP ENTRY	-	S

- = N/A    O = OPTION    S = STANDARD







**OPTIONAL PLATFORM ROTATION**

A manual rotate mechanism allows the operator to rotate up to 90° on the TZ™-34/20 platform, 45° in either direction. The hydraulic rotation on the TZ™-50 provides a 160° of platform rotation.



**HITCH COUPLER OPTIONS**

Choose the type of hitch that best meets your needs from a variety of options.



**DUAL FLASHING BEACONS**

Orange flashing lights warn workers when lift is moving or in operation.

# OPTIONS AND ACCESSORIES



## **DRIVE, SET, LIFT**

Choose the Drive and Set™ option to have ultimate flexibility in positioning your TZ™-50 exactly where you need it. When the platform is in the fully lowered position, you can drive the unit to the area where you need to work, deploy the outriggers and then raise the platform to the level needed. These quick, efficient operations increase your productivity on the job.



## **HYBRID DC/PETROL ENGINE**


Allows machine to charge in remote locations. (TZ™-50 only)

# SPECIFICATIONS

## TRAILER-MOUNTED Z™-BOOMS

MODEL	WORKING HEIGHT		HORIZONTAL REACH		LIFT CAPACITY*			
					STANDARD PLATFORM		WITH OPTIONAL PLATFORM ROTATION	
	Metric	US	Metric	US	Metric	US	Metric	US
<b>TRAILER-MOUNTED Z™-BOOMS</b>								
<b>TZ™-34/20</b>	12.36 m	40 ft	5.59 m	18 ft 4 in	200 kg	440 lbs	181 kg	400 lbs
<b>TZ™-50</b>	17.09 m	55 ft 6 in	8.89 m	29 ft 2 in	200 kg	440 lbs	200 kg	440 lbs

\*Lift capacity varies depending on options and country standards.





# Genie®

A TEREX BRAND

[www.genieindustries.com](http://www.genieindustries.com)

## Genie Australia – Toll free number 1800 788 633

**Brisbane (Head Office)**  
33 Kimberley Street  
Darra QLD 4076

**Sydney**  
74 Glendenning Road  
Glendenning NSW 2761

**Melbourne**  
374 Hammond Road  
Dandenong VIC 3175

**Perth**  
126 Sheffield Road  
Welshpool WA 6106

## Genie United States

18340 NE 76th Street  
P.O. Box 97030  
Redmond, Washington  
98073-9730

### WORLDWIDE MANUFACTURING AND DISTRIBUTION

Australia • Brazil • Caribbean • Central America • China • France • Germany • Italy • Japan • Korea • Mexico  
Southeast Asia • Spain • Sweden • United Arab Emirates • United Kingdom • United States

Effective Date: April 2012. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operators' Manual for instructions on the proper use of this equipment. Failure to follow the Operators Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks, or trade names of Terex Corporation, Terex South Dakota, Inc., and/or their subsidiaries in the USA and other countries. All rights reserved. Terex is a registered trademark of Terex Corporation in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. in the USA and many other countries. ©2009 Terex Corporation.